

AIRDRAULIC BIRCO GROUP PTY LTD

Sydney (H.O.): Unit 1, 33-35 Gibbes Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133

Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108

Fax: 61 7 3255 6199 Phone: 61 7 3255 6188 Melbourne: 165 Clayton Rd, Clayton VIC 3168 Phone: 61 3 9544 1711 Fax: 61 3 9544 2111 Perth: Unit 2, 73 Poole Street, Welshpool WA 6106 Phone: 61 8 9258 4144 Fax: 61 8 9258 4255

Website: www.abgpl.com.au Email: sales@abgpl.com.au



A B N 47 002 890 477 A C N 002 890 477







28VRS

- The components in all the Macdonald breakers are made from drop forged alloy steel, which gives maximum durability.
- The parts are interchangeable in the various models, thus minimising the spare parts inventory required to service the breakers.
- Macdonald breakers are designed to withstand the extreme demands of the hire and construction industry.
- The floating handle design reduces vibration to the operator by 85%.
- This means that an operator can use this for a much longer period of time (50 times longer) and still remain in the safe vibration exposure levels

Model	Weight	Air Cons @ 90 psi / 6 bar	Frequency	Stroke	Bore	Chuck
28VRS	28.5 kgs	26 l/sec	16 Hz	170 mm	44 mm	28 mm
	63 lbs	54 cfm	960 bpm	6.7"	1.73"	1 1/8"
348VRS	34 kgs	30 l/sec	21 Hz	146 mm	57 mm	28 mm
	75 lbs	65 cfm	1250 bpm	5.75"	2.25"	1 1/8"

85% Less Vibration

DISTRIBUTORS OF: